

# ROBNA MARKA SELEC

## ISPORUKA SA SKLADIŠTA U ZAGREBU

### Digitalni timer



**-600DT-**  
15 načina rada,  
8 vremenskih  
raspona, 1SPDT,  
20-240V

### Releji redoslijeda faza



**-600PSR-**  
greška faze, 154-  
500VAC, 1SPDT,  
17.5mm

### Analogni timer



**-600XU-**  
13 načina rada,  
10 vremenskih  
raspona, 1 SPDT,  
20-240V

### Releji propuštanja uzemljenja



**-900ELR-**  
10mA-30A,  
230VAC, 2SPDT,  
35mm DIN šina

### Sklopka vremenska



**-ATS2M1-**  
astronomska,  
digitalna, 1  
SPCT, 16A.  
230VAC, DIN Rail  
35mm

### Strujni transformator za ELR



**-CBCT-35-**  
unut. promjer  
35mm, omjer  
1000:1

### Strujni transformator za ELR



**-CBCT-70-**  
unut. promjer  
70mm, omjer  
1000:1



### Kontroler za hlađenje



**-CH403A-**  
izlaz: 10A relejni,  
pomoćni:  
12VDC/10mA,  
85-270V,  
36x72mm

### Brojač sati LCD



**-LT920A-**  
kontaktni ulaz,  
8 znamenaka,  
baterija, prednji  
gumb za reset

### Brojač sati LCD



**-LT920A-V-**  
naponski ulaz 24  
- 260VAC/DC,  
8 znamenaka,  
baterija, reset  
pre

### Brojač sati LCD



**-LT945A-**  
kontaktni ulaz,  
8 znamenaka,  
baterija

### Brojač sati LCD



**-LT945A-V-**  
naponski ulaz,  
24V - 260V  
AC/DC,  
8 znamenaka,  
baterija

### Brojač pulsa LCD



**-LXC900A-**  
kontaktni ulaz,  
8 znamenaka,  
baterija,  
Din šina

### Brojač pulsa LCD



**-LXC900A-V-**  
naponski ulaz,  
8 znamenaka,  
baterija, sivi



### Višenamjenski digitalni mjerač LCD



**-MFM383A-**  
3-fazni,  
7 mjerenja,  
EIA-485,  
85-270VAC, DIN

### Indikator procesa



**-PIC152A-**  
2xAlarm izlaz,  
85-270V, 1/8  
DIN

### Temperaturni PID kontroler



**-TC513BX-**  
48x48mm, 1x3  
znamenke, 85-  
270V, 1/16 DIN;  
dub. 76mm

### Kontroler temperaturni



**-TC544B-**  
pomoćni izlazni  
releji 5A,  
85-270V,  
1/16 DIN

### Sklopka vremenska



**-TS2M1-**  
50 ON i 50 OFF,  
1 SPCT, 16A.  
230VAC,  
DIN Rail 35mm

### Višenamjenski digitalni mjerač



**-VAF36A-**  
LCD, 3-fazni,  
napon/struja/  
frekvencija,  
96x96mm

### Kontroler nivoa vode



**-WLCA2M1-**  
analogni,  
85-270VAC,  
1SPDT, 35mm  
DIN šina

### Timer digitalni



**-XT546-**  
4 načina rada,  
9 vremenskih  
raspona, 2SPDT,  
85-270V